



Unit 1, 154-164 Renwick St, Marrickville

# SAFETY DATA SHEET

**NSW 2204 Australia** 

Freecall 1800 64 POOL Phone +61 2 9573 0777 (office hours)

This Revision Dated: March, 2025 Fax +61 2 9573 0566

## **SECTION 1 - IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

**Chemical nature:** Water solution of (mainly) acidic ingredients.

Trade Name: Aquapro Klenz

**Product Use:** Cleaner for pool and spa filtration systems

Creation Date: March, 2014

This version issued: March, 2025 and is valid for 5 years from this date. Poisons Information Centre: Phone 13 1126 from anywhere in Australia

## **SECTION 2 - HAZARDS IDENTIFICATION**

## **Statement of Hazardous Nature**

SUSMP Classification: S6

**ADG Classification:** Class 8: Corrosive Substances. **UN Number:** 1760, CORROSIVE LIQUID, N.O.S.





# GHS Signal word: DANGER.

Skin corrosion - category 1C

Specific target organ toxicity (single exposure) – category 3

## HAZARD STATEMENT:

H314: Causes severe skin burns and eye damage.

H335: May cause respiratory irritation.

#### **PREVENTION**

P102: Keep out of reach of children.

P261: Avoid breathing fumes, mists, vapours or spray.

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash contacted areas thoroughly after handling.

P271: Use only outdoors or in a well ventilated area.

P280: Wear protective gloves, protective clothing and eye or face protection.

## **RESPONSE**

P310: Immediately call a POISON CENTRE or doctor/physician.

P337: If eye irritation persists: seek medical attention.

P363: Wash contaminated clothing before reuse.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P391: Collect spillage.

P370+P378: Not combustible. Use extinguishing media suited to burning materials.

#### **STORAGE**

P405: Store locked up.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

## **DISPOSAL**

P501: If product can not be recycled, consider controlled incineration, or contact a specialist waste disposal company (see Section 13 of this SDS).

## **Emergency Overview**

Physical Description & colour: Clear, amber coloured liquid.

Odour: Mild odour.

Product name: Aquapro Filter Klenz



Unit 1, 154-164 Renwick St, Marrickville

# SAFETY DATA SHEET NSW 2204 Australia

Freecall 1800 64 POOL

Phone +61 2 9573 0777 (office hours)

This Revision Dated: March, 2025

Fax +61 2 9573 0566

Major Health Hazards: causes burns, may cause serious damage to eyes, respiratory tract irritant.

## **SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS**

Ingredients	CAS No	Conc,%	TWA (mg/m³)	STEL (mg/m³)
Sulfuric acid	7664-93-9	5-15	1	3
Phosphoric acid	7664-38-2	<5	1	3
Other non hazardous ingredients	secret	<5	not set	not set
Water	7732-18-5	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

## **SECTION 4 - FIRST AID MEASURES**

## **General Information:**

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

**Inhalation:** If irritation occurs, contact a Poisons Information Centre, or call a doctor. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. In severe cases, symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

**Skin Contact:** Quickly and gently, blot or brush away excess chemical. Remove contaminated clothing, shoes and leather goods.(e.g. watchbands, belts). Flush contaminated area with lukewarm, gently flowing water for at least 20-30 minutes, by the clock. If irritation persists, continue flushing. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this SDS and take their advice). Seek urgent medical attention.

**Eye Contact:** Quickly and gently, blot or brush away chemical. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 20-30 minutes, by the clock, while holding the eyelid(s) open. Neutral saline solution may be used as soon as it is available. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this SDS and take their advice). Take care not to rinse contaminated water into the unaffected eye or onto face. If irritation persists, repeat flushing. Call a Poisons Information Centre or a doctor urgently.

**Ingestion:** If swallowed, rinse mouth thoroughly with water and contact a Poisons Information Centre. Urgent hospital treatment is likely to be needed. Give activated charcoal if instructed.

## SECTION 5 - FIRE FIGHTING MEASURES

**Fire and Explosion Hazards**: There is no risk of an explosion from this product under normal circumstances if it is involved in a fire.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** Water fog or fine spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses.

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is little danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is liquid-tight chemical protective clothing and breathing apparatus.

Flammability Class: Does not burn.

## **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

**Accidental release:** In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Wear full protective chemically resistant clothing including eye/face protection, gauntlets and self contained breathing apparatus. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective

Product name: Aquapro Filter Klenz Page 2 of 6



Unit 1, 154-164 Renwick St, Marrickville

#### SAFETY DATA SHEET **NSW 2204 Australia**

Freecall 1800 64 POOL Phone +61 2 9573 0777 (office hours)

This Revision Dated: March, 2025

Fax +61 2 9573 0566

clothing include rubber, butyl rubber, neoprene, Teflon, polyethylene. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Because of the corrosiveness of this product, special personal care should be taken in any cleanup operation. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. Contaminated area may be neutralised by washing with weak or dilute alkali. Baking soda, washing soda and limestone are suitable. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

## **SECTION 7 - HANDLING AND STORAGE**

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this class of poison. Store in a cool, well ventilated area. Check containers periodically for corrosion and leaks. Containers should be kept closed in order to minimise contamination. Make sure that the product does not come into contact with substances listed under "Materials to avoid" in Section 10. If you keep more than 1000kg or 1000L of Corrosive Substances of Packaging Group III, you will require a license to do so. If you have any doubts, we suggest you contact your licensing authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

# SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: AS/NZS 1715, Protective Gloves: AS 2161, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: AS1336 and AS/NZS 1337, Occupational Protective Footwear: AS/NZS2210.

SWA Exposure Limits	TWA (mg/m³)	STEL (mg/m³)
Sulfuric acid	1	3
Phosphoric acid	1	3

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems. Ventilation: No special ventilation requirements are normally necessary for this product. However make sure that the work environment remains clean and that vapours and mists are minimised.

Eye Protection: Your eyes must be completely protected from this product by splash resistant goggles with face shield. All surrounding skin areas must be covered. Emergency eye wash facilities must also be available in an area close to where this product is being used.

**Skin Protection:** Because of the dangerous nature of this product, make sure that all skin areas are completely covered by impermeable gloves, overalls, hair covering, apron and face shield. See below for suitable material types. Protective Material Types: We suggest that protective clothing be made from the following materials: rubber, butyl rubber, neoprene, Teflon, polyethylene.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Eyebaths or eyewash stations and safety deluge showers should be provided near to where this product is being used.

## **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES:**

Physical Description & colour: Clear, amber coloured liquid.

Odour: Mild odour.

Product name: Aquapro Filter Klenz Page 3 of 6



**NSW 2204 Australia** 

Unit 1, 154-164 Renwick St, Marrickville

# SAFETY DATA SHEET

Phone +61 2 9573 0777 (office hours)

Freecall 1800 64 POOL P
This Revision Dated: March, 2025

5 Fax +61 2 9573 0566

**Boiling Point:** Approximately 100°C at 100kPa.

Flash point:
Upper Flammability Limit:
Lower Flammability Limit:
Does not burn.
Does not burn.

**Autoignition temperature:** Not applicable - does not burn.

Freezing/Melting Point: Approximately 0°C. Volatiles: Water component.

**Vapour Pressure:** 2.37 kPa at 20°C (water vapour pressure).

Vapour Density: No data.

**Specific Gravity:** Approx 1.10 at 20°C

**Water Solubility: pH:**Completely soluble in water.
Corrosive - pH about 0

Volatility: No data.
Odour Threshold: No data.
Evaporation Rate: No data.
Coeff Oil/water distribution: No data

Particle Characteristics: Not applicable to liquids.

## **SECTION 10 – STABILITY AND REACTIVITY**

**Reactivity**: Most strong acids react with inorganic and organic bases such as amines to form salts. They also react with many metals liberating hydrogen gas. These reactions are often rapid and sometimes liberate much heat. They can also decompose many organic materials such as esters, in a reaction called hydrolysis.

**Conditions to Avoid:** This product should be kept in a cool place, preferably below 30°C. Keep isolated from combustible materials.

Incompatibilities: bases, zinc, tin, aluminium and their alloys.

**Fire Decomposition:** Oxides of sulfur (sulfur dioxide is a respiratory hazard) and other sulfur compounds. Most will have a foul odour. Oxides of phosphorus and other phosphorus compounds.

Polymerisation: This product is unlikely to undergo polymerisation processes.

## **SECTION 11 - TOXICOLOGICAL INFORMATION**

**Local Effects:** 

**Target Organs:** There is no data to hand indicating any particular target organs.

## Classification of Hazardous Ingredients

Ingredient Health Hazard Statement Codes

Sulfuric acid H314

• Skin corrosion – category 1A

Phosphoric acid H314, H332

Skin corrosion – category 1B
Acute toxicity – category 4

## **Potential Health Effects**

## Inhalation

**Short term exposure:** Significant inhalation exposure is considered to be unlikely. However product is an inhalation irritant. Symptoms may include headache, irritation of nose and throat and increased secretion of mucous in the nose and throat. Other symptoms may also become evident, but they should disappear after exposure has ceased.

**Long Term exposure:** No data for health effects associated with long term inhalation.

Product name: Aquapro Filter Klenz Page 4 of 6



Unit 1, 154-164 Renwick St, Marrickville

# SAFETY DATA SHEET NSW 2204 Australia

Freecall 1800 64 POOL Phone +61 2 9573 0777 (office hours)

This Revision Dated: March, 2025 Fax +61 2 9573 0566

## **Skin Contact:**

**Short term exposure:** Available data indicates that this product is corrosive to the skin. Capable of causing moderate to severe burns with ulceration. Can penetrate to deeper layers of skin, resulting in third degree burns. Corrosion will continue until product is removed or neutralised. Severity depends on concentration and duration of exposure. Burns may not be immediately painful; the onset of pain may be minutes to hours.

Long Term exposure: No data for health effects associated with long term skin exposure.

# **Eye Contact:**

**Short term exposure:** This product is corrosive to eyes. It will cause severe pain, and corrosion of the eye and surrounding facial tissues. Unless exposure is quickly treated, permanent blindness and facial scarring is likely.

Long Term exposure: No data for health effects associated with long term eye exposure.

## Ingestion:

**Short term exposure:** Significant oral exposure is considered to be unlikely. However, this product is corrosive to the gastrointestinal tract. Capable of causing moderate to severe burns with ulceration. Can penetrate to deeper layers of skin, resulting in third degree burns. Corrosion will continue until product is removed or neutralised. Severity depends on concentration and duration of exposure.

Long Term exposure: No data for health effects associated with long term ingestion.

## Carcinogen Status:

**SWA:** No significant ingredient is classified as carcinogenic by SWA. **NTP:** No significant ingredient is classified as carcinogenic by NTP. **IARC:** No significant ingredient is classified as carcinogenic by IARC.

## **SECTION 12 - ECOLOGICAL INFORMATION**

This product does not degrade naturally.

## **SECTION 13 - DISPOSAL CONSIDERATIONS**

**Disposal:** Containers should be emptied as completely as practical before disposal. If possible, recycle containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site. Please do NOT dispose into sewers or waterways.

## **SECTION 14 - TRANSPORT INFORMATION**

UN Number: 1760, CORROSIVE LIQUID, N.O.S.

**Hazchem Code: 2X** 

Special Provisions: 223, 274

Limited quantities: ADG 7 specifies a Limited Quantity value of 5 L for this class of product.

Dangerous Goods Class: Class 8, Corrosive Substances.

Packing Group: Ⅲ

Packing Instruction: P001, IBC03, LP01

Class 8 Corrosive Substances shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances where the Toxic Substances are cyanides and the Corrosives are acids), 7 (Radioactive Substances), Foodstuffs and foodstuff empties. They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases), 2.2 (Non-Flammable, Non-Toxic Gases), 2.3 (Poisonous Gases), 3 (Flammable liquids), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 6 (Toxic Substances except where the Toxic Substances are cyanides and the Corrosives are acids) and 9 (Miscellaneous Dangerous Goods).

## **SECTION 15 - REGULATORY INFORMATION**

**AllC:** All of the significant ingredients in this product are compliant with AlCIS regulations. The following ingredients: Sulfuric acid, Phosphoric acid, are mentioned in the SUSMP.

Product name: Aquapro Filter Klenz Page 5 of 6



Unit 1, 154-164 Renwick St, Marrickville

# SAFETY DATA SHEET NSW 2204 Australia

Phone +61 2 9573 0777 (office hours)

This Revision Dated: March, 2025 Fax +61 2 9573 0566

## **SECTION 16 - OTHER INFORMATION**

Freecall 1800 64 POOL

#### See our web site at www.lo-chlor.com

This SDS contains only safety-related information. For other data see product literature.

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (July 2020) and GHS Revision 7

Copyright © Kilford & Kilford Pty Ltd, March, 2025.

http://www.kilford.com.au/ Phone (02)8321 8866

Product name: Aquapro Filter Klenz Page 6 of 6